

# Countertop water filters manufacturer

Countertop water filters are fully assembled and packaged in attractive retail cartons, complete with installation instructions. Filter housings are rated for pressures to 100PSI and temperature to 125F. 3/8" chrome inlet fitting, 3/8" diverter valve. White housings and white tubing are standard. Private labeling is available with minimum order required.

## FEATURES:

Fully assembled

Ready for installation

Shine spout

Adapter and fittings included

Ideal for private label marketing

- Single Under sink Water Filter
- 1. Single filter-two in one 10" (PPF 5um + GAC)
- 2. Pre-filter 5um remove rust, algae, small particulate etc.
- 3. Activated carbon remove bleach, chlorine, pesticide pigment etc.
- 4. Diverse water filter materials can be chosen to match the local water quality require.
- 5. Easily connects to faucet with diverter valve
  
- Double Countertop water filter
- 1. Twin water filter-10" PPF 5um + 10" GAC (or CTO)
- 2. Pre-filter 5um remove rust, algae, small particulate etc.
- 3. Activated carbon remove bleach, chlorine, pesticide pigment etc.
- 4. Diverse water filter materials can be chosen to match the local water quality require.
- 5. Easily connects to faucet with diverter valve s
  
- Three Stages Countertop water filter
- 1. Triple water filter-10" PPF 5um + 10" GAC+10" CTO (or ION RESIN)
- 2. Pre-filter 5um remove rust, algae, small particulate etc.
- 3. Activated carbon remove bleach, chlorine, pesticide pigment etc.
- 4. Ion resin absorbs  $\text{CaCO}_3$  in water, reducing incrustation on pipes and prevents calculus
- 5. Diverse water filter materials can be chosen to match the local water quality require.
- 6. Easily connects to faucet with diverter valve

## Contact us

Cixi Waterhoh Water Filtration, Inc.

**Address** :Jinzhu Sanbei Town Cixi City Zhejiang 31511 China

**E-mail** info@cnwaterfilter.com

**Website**: <http://www.cnwaterfilter.com/>