

Pleated Water Filters Replacement Cartridges manufacturer

Water Filters Replacement Cartridges is constructed of durable, spun bond non-woven, reusable polyester fabric which allows for several uses. The media has been pleated to maximize its dirt holding capacity and extend the time period between changes. The media chemical and bacteria resistance makes these cartridges suitable for most light industrial and well water applications.

Features	<ul style="list-style-type: none"> • Low pressure drop; • Pleated design and more filter area for increased contaminant removed; • Long filter runs, longer life used; • The polyester media may be cleaned and cartridge maybe re-used; • Thermally-bonded construction with media, end caps and inner code heat sealed together 		
RECOMMENDED APPLICATIONS	<ul style="list-style-type: none"> • Pre-filter of drinking water filter system • Swimming pool water filter system • Pre-filter of reverse osmosis system and general commercial water filter system • Electroplating, etching and image development processes in PCB industry. • Filtration of electroplating fluid in conventional electroplating industry • Pre-filter of DI & RO water filtration system for industry. • Filtration of medium & low viscosity fluids of chemical. • Filtration of water for manufacturing processes and recycled water. 		
OPERATION CONDITIONS	<table border="0" style="width: 100%;"> <tr> <td style="width: 50%;">Maximum operating pressure 80psid</td> <td style="width: 50%;">Maximum operating Temperature 40; C ~80; C</td> </tr> </table>	Maximum operating pressure 80psid	Maximum operating Temperature 40; C ~80; C
Maximum operating pressure 80psid	Maximum operating Temperature 40; C ~80; C		
RECOMMENDED APPLICATIONS	<ul style="list-style-type: none"> • Media: Non-Woven Polyester Fabric • Non-Woven Polypropylene Fabric • End Caps: Vinyl Plastisol • Inner Core: Polypropylene • Outer sheath: Polypropylene 		
RETENTION RATINGS (µ m)	Nominal 1, 5, 10, 20, 30, 50, 75 micron		
SPECIFICATIONS	<ul style="list-style-type: none"> • Inner diameter: 28mm • Outer diameter: 68mm~112mm • Length:127mm~762mm 		